SUPER ★ TALENT®
THE BEST MEMORY

DuraDrive ET3

IDE/PATA Solid State Drive

Super Talent's DuraDrive ET3 displays the next generation of industrial data storage solutions through enhanced durability, reliability and performance environments considered "too harsh" for a standard drive.

Supporting access times of 0.1ms, the DuraDrive can reach read and writes speeds of up to 110/95 MB/sec. With ECC/EDC support, bad bit management firmware and patented wear leveling technology, the DuraDrive ET3 is sure to fit your computing needs.

Featuring the industry standard 2.5" form factor and IDE/PATA interface, the DuraDrive ET3 is 100% interchangeable with conventional 2.5" IDE/PATA hard drives.

This SSD is geared specifically for applications that require high shock, vibration, and/or reliability. Examples include:
• Medical Industry • Embedded/Industrial Systems
• Enterprise Computing • Aerospace • Casino Gaming

Physical Specifications

	DuraDrive ET3
Form Factor	2.5"
Capacity	32-256GB(MLC),16-64GB(SLC)
Dimensions	100.2 x 69.85 x 9.5 mm
Interface	IDE/PATA
NAND Flash	MLC/SLC
Power Supply	5V ± 10%
Package	Complete metal housing

Environmental Specifications

Shock (Operating)	1500G
Vibration (Operating)	16G
Operating Temperature (Industrial)	-40°C ~ 85°C
Operating Temperature (Commercial)	0°C ~ 70°C

Ordering information

MLC	
32 GB	FE8032MD2D
64 GB	FE8064MD2D
128 GB	FE8128MD2D
256 GB	FE8256MD2D

SLC	
16 GB	FEK016MD2D
32 GB	FEK032MD2D
64 GB	FEK064MD2D

© 2014 Super Talent Technology. Specifications subject to change without notice. US patent #6,547,130 #7,243,185 #7,301,776 #7,318,117 and others apply.
*Usable capacity may be less than specified after formatting.